

## SLANT FIN LYNX HIGH EFFICIENT GAS BOILER



COMPACT, POWERFUL AND AGILE. SLANT FIN'S NEW LYNX SEALED COMBUSTION GAS BOILER PURRS WITH PERFORMANCE. OPERATES AT 95% AFUE MAXIMIZING FUEL SAVINGS. COMPACT, LIGHT WEIGHT FOR EASY HANDLING. ADVANCED DESIGN CAST ALUMINUM HEAT EXCHANGER SETS A NEW STANDARD FOR RELIABILITY.

THIS NEW GENERATION DESIGN INCORPORATES A CAST ALUMINUM HEAT EXCHANGER THAT IS CORROSION RESISTANT. ITS HIGH THERMAL CONDUCTIVITY BRINGS WARMTH QUICKLY TO THE LIVING SPACE.

- 94% AFUE
- Advanced design long life cast aluminum heat exchanger
- 85,000 Btuh input
- 3.4:1 modulation provides input range of 5,000 to 85,000 Btuh
- Floor standing (33-7/8"H x 23-5/8"W x 23-3/4"D)
- Natural or L.P. gas
- PVC/CPVC vent pipe — up to 100 ft. equivalent length
- All connections on top
- Quiet
- Low NOx — friendly to the environment
- Must Use Aluminum Safe Antifreeze
- Ideal for radiant, baseboard, DHW or mixed applications

**1 SIZE AVAILABLE**  
**MODEL LX-85A \$3056.00**

## SLANT FIN LYNX HIGH EFFICIENT GAS BOILER



COMPACT, POWERFUL AND AGILE. SLANT FIN'S NEW LYNX SEALED COMBUSTION GAS BOILER PURRS WITH PERFORMANCE. OPERATES AT 95% AFUE MAXIMIZING FUEL SAVINGS. COMPACT, LIGHT WEIGHT FOR EASY HANDLING. ADVANCED DESIGN CAST ALUMINUM HEAT EXCHANGER SETS A NEW STANDARD FOR RELIABILITY.

THIS NEW GENERATION DESIGN INCORPORATES A CAST ALUMINUM HEAT EXCHANGER THAT IS CORROSION RESISTANT. ITS HIGH THERMAL CONDUCTIVITY BRINGS WARMTH QUICKLY TO THE LIVING SPACE.

- 94% AFUE
- Advanced design long life cast aluminum heat exchanger
- 85,000 Btuh input
- 3.4:1 modulation provides input range of 5,000 to 85,000 Btuh
- Floor standing (33-7/8"H x 23-5/8"W x 23-3/4"D)
- Natural or L.P. gas
- PVC/CPVC vent pipe — up to 100 ft. equivalent length
- All connections on top
- Quiet
- Low NOx — friendly to the environment
- Must Use Aluminum Safe Antifreeze
- Ideal for radiant, baseboard, DHW or mixed applications

**1 SIZE AVAILABLE**  
**MODEL LX-85A \$3056.00**