

SPECIFICATIONS	MODEL 700	MODEL 900	MODEL 950
Max. compensated hardness:	70 grains per gallon (gpg)	90 grains per gallon (gpg)	35 grains per gallon (gpg)
Maximum hardness removed:	22,000 grains	36,400 grains	22,000 grains
Maximum ferrous iron reduction:	10 ppm	10 ppm	0
Minimum pH (standard units):	7	7	7
Salt used per regeneration:	2.5 lbs.	3 lbs.	2.5 lbs.
Length of regeneration cycle:	17 minutes	20 minutes	17 minutes
Water used per regeneration:	12 gallons	14 gallons	14 gallons
Plumbing connections:	¾" or 1" NPT	¾" or 1" NPT	¾" or 1" NPT
Valve size:	1"	1"	1"
Salt storage capacity:	120 lbs.	160 lbs.	160 lbs.
Electrical requirements:	110/120 VAC, 12V 50/60 cycle	110/120 VAC, 12V 50/60 cycle	110/120 VAC, 12V 50/60 cycle
Max. water temperature:	120°	120°	120°
Water pressure (min. - max. psi):	20 - 120	20 - 120	20 - 120
Footprint (WxD):	14 ¾" x 18 ¾"	14 ¾" x 18 ¾"	14 ¾" x 18 ¾"
Height:	25 ¾"	30 ¾"	30 ¾"
Shipping Weight:	85 lbs.	105 lbs.	105 lbs.

Operational maintenance and replacement requirements are essential for the product to perform to specification.

COST: \$479.99

Have DJ's Do Your Installation

\$195.00 plus Materials

\$35.00 Disposal of Old Unit

If no softener loop estimated additional charge \$100.00

SPECIFICATIONS	MODEL 700	MODEL 900	MODEL 950
Max. compensated hardness:	70 grains per gallon (gpg)	90 grains per gallon (gpg)	35 grains per gallon (gpg)
Maximum hardness removed:	22,000 grains	36,400 grains	22,000 grains
Maximum ferrous iron reduction:	10 ppm	10 ppm	0
Minimum pH (standard units):	7	7	7
Salt used per regeneration:	2.5 lbs.	3 lbs.	2.5 lbs.
Length of regeneration cycle:	17 minutes	20 minutes	17 minutes
Water used per regeneration:	12 gallons	14 gallons	14 gallons
Plumbing connections:	¾" or 1" NPT	¾" or 1" NPT	¾" or 1" NPT
Valve size:	1"	1"	1"
Salt storage capacity:	120 lbs.	160 lbs.	160 lbs.
Electrical requirements:	110/120 VAC, 12V 50/60 cycle	110/120 VAC, 12V 50/60 cycle	110/120 VAC, 12V 50/60 cycle
Max. water temperature:	120°	120°	120°
Water pressure (min. - max. psi):	20 - 120	20 - 120	20 - 120
Footprint (WxD):	14 ¾" x 18 ¾"	14 ¾" x 18 ¾"	14 ¾" x 18 ¾"
Height:	25 ¾"	30 ¾"	30 ¾"
Shipping Weight:	85 lbs.	105 lbs.	105 lbs.

Operational maintenance and replacement requirements are essential for the product to perform to specification.

COST: \$479.99

Have DJ's Do Your Installation

\$195.00 plus Materials

\$35.00 Disposal of Old Unit

If no softener loop estimated additional charge \$100.00